FLOORCARE

1715/00 5 LITRE

FLOOR MAINTAINER INFORMATION SHEET

FLOOR A maintenance product for floors previously coated with a metallised floor polish. DIFECTIONS For damp mapping dilux: 1:20 with water. Mog floor with this solution, rinse the wire into a bucket of clearn water and allow to day. Then machine buffer of pass the machine over this beam. For spray halfing district the selection of the selection of the pass should clear, day and ultime the flow. On our over apply the selection of boar male the selection of the variety of the pass should be mapped or a crubbed with a mild solvent-based delimine the flow. On our over apply and on our disruption of their maintains of flow maintains of the pass o

USE:

A maintenance product for floors previously coated with a metallised floor polish.







DIRECTIONS:

For damp mopping dilute 1:20 with water. Mop floor with this solution, rinse the dirt into a bucket of clean water and allow to dry. Then machine buff to restore the shine. For spray buffing dilute 1:8 with water. Spray a small amount onto the floor and pass the machine over this area, three or four passes should clean, dry and shine the floor. Do not over apply and do not attempt to spray buff very dirty floors, these should be mopped or scrubbed with a mild solvent-based detergent prior to application of floor maintainer. DO NOT USE on unsealed wood or cork floor coverings. PROTECT FROM FROST.

TECHNICAL:

State: Liquid Colour: Pink

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble Viscosity: Non-viscous

Boiling point/range°C: 100 Flash point°C: >93 pH Level: 8

PERSISTENCE AND DEGRADABILITY: Biodegradable.

